

# FORD (USA) TAURUS D186 TAURUS 2.5 L, GL (1991-1992)

**ENGINE**

Capacity: 4,3 liter, Filter capacity: 0,5 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Change every 12000 km/ 6 months*

## USE

Severe

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Change every 4800 km/ 3 months***TRANSAXLE AUTOMATIC**

Capacity: 8 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Matic 4016**

## PRODUCT RECOMMENDATION 2

**ATF Dexron II-D****HYDRAULIC BRAKE/CLUTCH SYSTEM**

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Change every 48000 miles/ 36 months***POWER STEERING**

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**ATF Almirol**

## PRODUCT RECOMMENDATION 2

**ATF Dexron II-D**

## PRODUCT RECOMMENDATION 3

**ATF-F (Ford)***Check every 1 months*

## PRODUCT RECOMMENDATION

**FORD (USA) TAURUS D186 TAURUS 2.5 L,  
GL (1991-1992)****COOLING SYSTEM**

Capacity: 8 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant SP 18****PRODUCT RECOMMENDATION 2****Coolant -38 Organic NF***Change every 48000 miles/ 36 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*