FORD (USA) TAURUS D3 TAURUS 3.5 V6 (2010-2011)



ENGINE Duratec 35 Capacity: 5,2 liter	
use Normal	CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Duranza ECO 5W-20	

Change every 10000 miles/ 12 months

TRANSAXLE AUTOMATIC 6F50 Capacity: 10,3 liter	6/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	
Change every 150000 miles		

TRANSAXLE AUTOMATIC 6F55 Capacity: 11 liter	6/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	
Change every 150000 miles	•	

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

POWER STEERING Capacity: 0-0 liter (Between min and max.)			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
SP Matic 2032			

FORD (USA) TAURUS D3 TAURUS 3.5 V6 (2010-2011)



COOLING SYSTEM Capacity: 10,5 liter		
USE		CLIMATE
Green coolant		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
USE		CLIMATE
Orange coolant		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.