PRODUCT RECOMMENDATION

FORD (USA) WINDSTAR WINDSTAR 3.0 V6 (1994-1998)

ENGINE
Capacity: 4,25 liter, Filter capacity: 0,25 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		

Check every 3000 km, change every 10000 km/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Emperol 10W-40	**Bi-Turbo 15W-40**	

Check every 3000 km, change every 10000 km/ 12 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		

Check every 3000 km, change every 10000 km/ 12 months

TRANSAXLE AUTOMATIC 4/1
Capacity: 8,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4016	**ATF Dexron II-D**	

Check every 10000 km/ 12 months, change every 100000 km

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Change every 60000 km/ 36 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

FORD (USA) WINDSTAR WINDSTAR 3.0 V6 (1994-1998)

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4016	**ATF Dexron II-D**	

Check every 10000 km/ 12 months

COOLING SYSTEM

Capacity: 13 liter, Capacity: 13,2 liter (with 4 zone airconditioning system)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	**Coolant -38 Organic NF**	

Change every 60000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367