GMC (USA / CAN) ACADIA GMT960 ACADIA 3.6 V6 AWD (2008-2010)



| ENGINE LLT Capacity: 5,2 liter | | | |
|--------------------------------|--------------------------|----------|--|
| USE Flexible (max) | | CLIMATE | |
| | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Presteza MSP 5W-30 | Xedoz FE 5W-30 | | |
| | | | |

Change every 12 months

| | CLIMATE | |
|--------------------------|----------|------------------------------------|
| | Moderate | |
| PRODUCT RECOMMENDATION 2 | | |
| Syngear TDL 75W-90 | | |
| | | Moderate PRODUCT RECOMMENDATION 2 |

| TRANSAXLE AUTOMATIC 6/1 Capacity: 5 liter | | |
|---|------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4036 | | |
| Check every 12 months, change every 10 | 0000 miles | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4036 | | |

Check every 12 months, change every 50000 miles

| TRANSFERBOX (4X4) | | |
|---------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Gear 1011 | Syngear TDL 75W-90 | |
| Change every 150000 miles | | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Gear 1011 | Syngear TDL 75W-90 | |
| Change every 50000 miles | | |
| | | |

Dollegoorweg 15

7602 EC Almelo

GMC (USA / CAN) ACADIA GMT960 ACADIA 3.6 V6 AWD (2008-2010)



| HYDRAULIC BRAKE SYSTEM | | | |
|--------------------------|--|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | | | |
| Drauliquid DOT 3 | | | |
| Check every 12 months | | | |

| POWER STEERING | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Matic 2032 | |

| COOLING SYSTEM Capacity: 10,8 liter | | | |
|-------------------------------------|--------------------------|----------|--|
| use Normal | | CLIMATE | |
| | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant SP 15 | Coolant SP 15+ | | |
| 01 450000 11 /00 | 4 | <u>'</u> | |

Change every 150000 miles/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.