

GMC (USA / CAN) YUKON / XL GMT922/932

YUKON 2500 5.3 V8 AWD (2011-2012)

**ENGINE** LMG/LC9

Capacity: 5,7 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30*Check every 12 months, change every 24 months***DIFFERENTIAL FRONT (4x4)**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90**DIFFERENTIAL REAR**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90**TRANSFERBOX (4X4)**

Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Change every 97500 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Change every 45000 miles*

GMC (USA / CAN) YUKON / XL GMT922/932

YUKON 2500 5.3 V8 AWD (2011-2012)

**TRANSMISSION AUTOMATIC 6L80-E 6/1**

Capacity: 11,7 liter (Dry fill), Capacity: 9,9 liter (Overhaul capacity), Capacity: 5,7 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Change every 97500 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Change every 45000 miles***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 12 months, change every 24 months***POWER STEERING**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032**COOLING SYSTEM**

Capacity: 17,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15

PRODUCT RECOMMENDATION 2

Coolant SP 15+*Check every 12 months, change every 150000 miles/ 60 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.