HONDA (USA / CAN) PILOT YF3/YF4 PILOT 3.5 V6 4WD (2010-2011)



ENGINE J35Z4 Capacity: 5 liter (Dry fill), Capacity: 4,3 liter (Service fill), Filter capacity: 0,3 liter				
USE		CLIMATE		
Flexible (max)		Moderate		
PRODUCT RECOMMENDATION 1				
Duranza ECO 5W-20				
Change every 12 months				

DIFFERENTIAL REAR

Capacity: 2,9 liter (Dry fill), Capacity: 2,6 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSAXLE AUTOMATIC 5/1 Capacity: 8,1 liter (Dry fill), Capacity: 3,4 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4026				

	CLIMATE	
	Moderate	
PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90		
		PRODUCT RECOMMENDATION 2

HYDRAULIC BRAKE SYSTEM			
USE	CLIMATE		
Flexible (max)	Moderate		
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3			
Change every 36 months	·		

POWER STEERING

We are unable to give a standard recommendation for this component. Please contact our service department.

HONDA (USA / CAN) PILOT YF3/YF4 PILOT 3.5 V6 4WD (2010-2011)



COOLING SYSTEM Capacity: 9,4 liter (Dry fill), Capacity: 7,5 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 14+				

AIRCONDITIONING

Capacity: 600-650 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.