

HONDA (USA / CAN) ACCORD IX

CR2/CR3/CT1/CT2 ACCORD 2.4 (2012-2017)

**ENGINE K24W**

Capacity: 4,2 liter, Filter capacity: 0,2 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-20*Change every 12 months***TRANSAXLE CVT 1/1**

Capacity: 3,7 liter

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4016*Change every 25000 miles*

USE	CLIMATE
Flexible (on board maintenance system)	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4016**TRANSAXLE MANUAL 6/1**

Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015**HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Change every 36 months*

HONDA (USA / CAN) ACCORD IX

CR2/CR3/CT1/CT2 ACCORD 2.4 (2012-2017)

**COOLING SYSTEM**

Capacity: 6,3 liter (Service fill)

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

AIRCONDITIONING

Capacity: 425-475 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.