HONDA (USA / CAN) CR-V RE3/RE4 CR-V 2.4 4WD (2010-2011)



| ENGINE K24Z6 Capacity: 5,3 liter (Dry fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,2 liter | | | | |
|--|--|----------|--|--|
| USE | | CLIMATE | | |
| Flexible (max) | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | | |
| Presteza MSP 0W-20 | | | | |
| Change avery 12 months | | | | |

Change every 12 months

DIFFERENTIAL REAR

Capacity: 1,4 liter (Dry fill), Capacity: 1,2 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

| TRANSAXLE AUTOMATIC 5/1 Capacity: 7 liter (Dry fill), Capacity: 2,5 liter (Service fill) | | | | |
|---|-----|----------|--|--|
| USE | | CLIMATE | | |
| Severe | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | | |
| SP Matic 4036 | | | | |
| Change every 30000 miles/24 months | | | | |
| USE | | CLIMATE | | |
| Flexible (on board maintenance syste | em) | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | | |
| SP Matic 4036 | | | | |

| HYDRAULIC BRAKE SYSTEM | |
|--------------------------|----------|
| USE | CLIMATE |
| Flexible (max) | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid DOT 3 | |
| Change every 36 months | · |

POWER STEERING

We are unable to give a standard recommendation for this component. Please contact our service department.

HONDA (USA / CAN) CR-V RE3/RE4 CR-V 2.4 4WD (2010-2011)



| COOLING SYSTEM Capacity: 7 liter (Dry fill), Capacity: 0,6 liter (Reservoir), Capacity: 5,9 liter (Service fill) | | | | |
|---|-----|--------------------|--|--|
| use Flexible (on board maintenance syst | em) | сымате Moderate | | |
| PRODUCT RECOMMENDATION 1 Coolant SP 14+ | | | | |

AIRCONDITIONING

Capacity: 440-490 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.