

HONDA (USA / CAN) ELEMENT YH1/YH2

ELEMENT 2.4 AWD (USA) (2003-2004)

**ENGINE K24A4**

Capacity: 5,3 liter (Initial fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Duranza ECO 5W-20	Asyntho 5W-30

Change every 10000 miles/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Duranza ECO 5W-20	Asyntho 5W-30

*Change every 5000 miles/ 6 months***DIFFERENTIAL REAR (4x4)**

Capacity: 1,2 liter (Initial fill), Capacity: 1 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSAXLE AUTOMATIC 4/1

Capacity: 7,2 liter (Overhaul capacity), Capacity: 3,1 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 4026	

Change every 90000 miles/ 60 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 4026	

Change every 30000 miles/ 24 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 4026	

Change every 120000 miles/ 72 months

USE	CLIMATE
First change only, severe	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 4026	

Change every 60000 km/ 36 months

HONDA (USA / CAN) ELEMENT YH1/YH2

ELEMENT 2.4 AWD (USA) (2003-2004)

**TRANSAXLE MANUAL 5/1**

Capacity: 2,3 liter (Initial fill), Capacity: 1,9 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Change every 120000 miles/ 72 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Change every 60000 km/ 36 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Change every 36 months***POWER STEERING**

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 7,1-7,2 liter (Initial fill), Capacity: 5,4-5,5 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Change every 60000 miles/ 60 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Change every 120000 miles/ 120 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.