

HONDA (USA / CAN) ELEMENT YH1/YH2

ELEMENT 2.4 AWD (2007-2007)

**ENGINE K24A8**

Capacity: 5,3 liter (Initial fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,2 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Duranza ECO 5W-20***Change every 12 months***DIFFERENTIAL REAR (4x4)**

Capacity: 1,2 liter (Initial fill), Capacity: 1 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSAXLE AUTOMATIC 5/1

Capacity: 7,2 liter (Overhaul capacity), Capacity: 2,5 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4026****USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4026***Change every 30000 miles***USE**

First change only, severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4026***Change every 60000 miles***TRANSAXLE MANUAL 5/1**

Capacity: 2,3 liter (Initial fill), Capacity: 1,9 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 5015**

HONDA (USA / CAN) ELEMENT YH1/YH2

ELEMENT 2.4 AWD (2007-2007)



HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Change every 36 months

POWER STEERING

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 7,2-7,3 liter (Initial fill), Capacity: 5,1-5,2 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.