HONDA (USA / CAN) PILOT YF5/YF6 PILOT 3.5 V6 AWD (2015-2022)



ENGINE J35Y6 Capacity: 5,4 liter (Service fill), Filter capacity: 0,3 liter			
USE		CLIMATE	
Flexible (max)		Moderate	
PRODUCT RECOMMENDATION 1			
Presteza MSP 0W-20			
Change every 12 months			

DIFFERENTIAL REAR

Capacity: 1,82 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSFERBOX (4x4) Capacity: 0,43 liter (Service fill)			
use Flexible (on board maintenance system)		CLIMATE	
		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90	

TRANSMISSION AUTOMATIC PLXA 6/1 Capacity: 3,1 liter			
USE		CLIMATE	
Flexible (on board maintenance syst	em)	Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			

TRANSMISSION AUTOMATIC Q5EZ 9/1 Capacity: 3,3 liter			
USE		CLIMATE	
Flexible (on board maintenance system)		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 2034			

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 36 months	

HONDA (USA / CAN) PILOT YF5/YF6 PILOT 3.5 V6 AWD (2015-2022)



COOLING SYSTEM Capacity: 7,13-7,4 liter (Service fill)		
USE		CLIMATE
Flexible (on board maintenance syst	em)	Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

AIRCONDITIONING COMPRESSOR

Capacity: 123-153 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 605-725 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.