

HONDA (EU) ACCORD III CA ACCORD, - AERODECK 2.0i (1986-1987)

**ENGINE A20**

Capacity: 3,5 liter, Filter capacity: 0,5 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Emperol 10W-40 | Bi-Turbo 15W-40 | HDX 20W-50 |

Change every 10000 km/ 6 months

| USE | | CLIMATE |
|--------------------------|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Asyntho 5W-30 | | |

*Change every 10000 km/ 6 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 2,8 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF-A | | |

*Change every 40000 km/ 48 months***TRANSAXLE MANUAL 5/1**

Capacity: 2,4 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Asyntho 5W-30 | Emperol 10W-40 | Bi-Turbo 15W-40 |

*Check every 10000 km/ 6 months, change every 40000 km/ 24 months***HYDRAULIC BRAKE SYSTEM**

| USE | | CLIMATE |
|----------------------------------|---------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 |

*Change every 40000 km/ 48 months***POWER STEERING**

Capacity: 1,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HONDA (EU) ACCORD III CA ACCORD, - AERODECK 2.0i (1986-1987)



COOLING SYSTEM

Capacity: 7 liter (+ automatic transmission/transaxle), Capacity: 6,4 liter (+ manual transmission/transaxle)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

Change every 40000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.