PRODUCT RECOMMENDATION

HONDA (EU) CIVIC III AG/AH/AJ/AK/AL/AM/AU CIVIC 1.3 (1985-1987)

ENGINE EV
Capacity: 3,5 liter, Filter capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	**Bi-Turbo 15W-40**	**HDX 20W-50**
Change every 10000 km/ 6 months		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Change every 10000 km/ 6 months		

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	**Bi-Turbo 15W-40**	**HDX 20W-50**
Change every 5000 km/ 3 months		

USE		CLIMATE
Severe		Arctic
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Change every 5000 km/ 3 months		

TRANSAXLE AUTOMATIC 3/1
Capacity: 2,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF-A		
Change every 40000 km/ 48 months		

TRANSAXLE AUTOMATIC 4/1
Capacity: 2,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF-A		
Change every 40000 km/ 48 months		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

HONDA (EU) CIVIC III AG/AH/AJ/AK/AL/AM/AU CIVIC 1.3 (1985-1987)

TRANSAXLE MANUAL 5/1
Capacity: 2,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	**Emperol 10W-40**	**Bi-Turbo 15W-40**

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	**Drauliquid DOT 3**

Change every 40000 km/ 48 months

POWER STEERING
Capacity: 1,2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM
Capacity: 4,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 40000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367