

HONDA (EU) CIVIC V EG/EH/EJ CIVIC 1.6 VTI (1992-1995)



ENGINE B16A2
Capacity: 4 liter

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Change every 5000 km/ 6 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Emperol 10W-40

PRODUCT RECOMMENDATION 2

Bi-Turbo 15W-40

PRODUCT RECOMMENDATION 3

HDX 20W-50

Change every 5000 km/ 6 months

USE	CLIMATE
Severe	Arctic

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

Change every 5000 km/ 6 months

USE	CLIMATE
->1993	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Change every 10000 km/ 6 months

USE	CLIMATE
->1993	Moderate

PRODUCT RECOMMENDATION 1

Emperol 10W-40

PRODUCT RECOMMENDATION 2

Bi-Turbo 15W-40

PRODUCT RECOMMENDATION 3

HDX 20W-50

Change every 10000 km/ 6 months

USE	CLIMATE
->1993	Arctic

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

Change every 10000 km/ 6 months

USE	CLIMATE
1994->	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Check every 3000 km, change every 10000 km/ 12 months

HONDA (EU) CIVIC V EG/EH/EJ CIVIC 1.6 VTI (1992-1995)



USE		CLIMATE
1994->		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Bi-Turbo 15W-40	HDX 20W-50

Check every 3000 km, change every 10000 km/ 12 months

USE		CLIMATE
1994->		Arctic
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		

Check every 3000 km, change every 10000 km/ 12 months

TRANSAXLE MANUAL Y 21 (S21) 5/1 Capacity: 2,2 liter

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	Emperol 10W-40	

Change every 20000 km/ 12 months

USE		CLIMATE
->1993		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	Emperol 10W-40	

Change every 40000 km/ 48 months

USE		CLIMATE
1994->		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	Emperol 10W-40	

Change every 60000 km/ 36 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 40000 km/ 48 months

POWER STEERING

Capacity: 1,1 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HONDA (EU) CIVIC V EG/EH/EJ CIVIC 1.6 VTI (1992-1995)



COOLING SYSTEM

Capacity: 4,8 liter (Initial fill), Capacity: 3,9 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

Change every 80000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.