

HONDA (EU) CIVIC VI EJ/EK/EM/MA/MB/MC

CIVIC 1.6 VTI (1995-2001)

**ENGINE**

Capacity: 4,8 liter (Initial fill), Capacity: 4 liter (Service fill), Filter capacity: 0,3 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Check every 3000 km, change every 10000 km/ 12 months*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40*Check every 3000 km, change every 10000 km/ 12 months*

USE

Severe

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 5000 km/ 6 months*

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40*Change every 5000 km/ 6 months***TRANSAXLE MANUAL 5/1**

Capacity: 2,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Check every 10000 km/ 12 months, change every 60000 km/ 36 months***HYDRAULIC BRAKE SYSTEM**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Change every 40000 km/ 48 months*

HONDA (EU) CIVIC VI EJ/EK/EM/MA/MB/MC

CIVIC 1.6 VTI (1995-2001)

**POWER STEERING**

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 4,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

Change every 80000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.