

# HONDA (EU) CIVIC IX FK/FB/FG CIVIC 2.2I-DTEC (2012-2017)

**ENGINE N22B4**

Capacity: 6,8 liter (Dry fill), Capacity: 5,5-5,9 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza MSP 0W-30</b>	<b>Presteza MSP 0W-30</b>	<b>Avanza MSP 0W-30</b>

*Change every 20000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza MSP 0W-30</b>	<b>Presteza MSP 0W-30</b>	<b>Avanza MSP 0W-30</b>

*Change every 10000 km/ 6 months***TRANSAXLE MANUAL 6/1**

Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Gear 5015</b>		

*Check every 20000 km/ 12 months, change every 120000 km/ 96 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

*Check every 20000 km/ 12 months, change every 36 months*

# HONDA (EU) CIVIC IX FK/FB/FG CIVIC 2.2I-DTEC (2012-2017)



## COOLING SYSTEM

Capacity: 6,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 14+**

Check every 20000 km/ 12 months, change every 60000 km/ 36 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 14+**

Check every 20000 km/ 12 months, change every 100000 km/ 60 months

## AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*