

HONDA (EU) CR-V II RD4/RD5/RD6/RD7 CR-V 2.4I-VTEC 4WD (2002-2007)

**ENGINE K24A1**

Capacity: 5,3 liter (Dry fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-20	Avanza MSP 0W-30	Helar 0W-40

Change every 20000 km/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-20	Avanza MSP 0W-30	Helar 0W-40

*Check every 3000 km, change every 10000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 1,4 liter (Dry fill), Capacity: 1,2 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSAXLE AUTOMATIC 4/1

Capacity: 7,2 liter (Dry fill), Capacity: 3,2 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 20000 km/ 12 months, change every 80000 km/ 48 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 20000 km, change every 40000 km/ 24 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 20000 km/ 12 months, change every 120000 km/ 96 months

USE	CLIMATE
Severe, first change only	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 20000 km/ 12 months, change every 60000 km/ 48 months

HONDA (EU) CR-V II RD4/RD5/RD6/RD7 CR-V 2.4I-VTEC 4WD (2002-2007)



TRANSAXLE MANUAL 5/1

Capacity: 2,3 liter (Dry fill), Capacity: 1,9 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

Check every 20000 km/ 12 months, change every 120000 km/ 96 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3

Check every 20000 km/ 12 months, change every 36 months

POWER STEERING

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 5,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 20000 km/ 12 months, change every 200000 km/ 120 months

AIRCONDITIONING

Capacity: 480-530 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

Capacity: 130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.