# HONDA (EU) CR-V III RE CR-V 2.4I-VTEC 2WD (2007-2011)



<b>ENGINE</b> K24Z1/K24Z2 Capacity: 5,3 liter (Dry fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,2 liter			
use Normal		climate Moderate	
Presteza MSP 0W-20	Presteza MSP 0W-30	Duranza LSP 5W-30	
Change every 20000 km/ 12 month	s		
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Presteza MSP 0W-20	Presteza MSP 0W-30	Duranza LSP 5W-30	
Change every 10000 km/ 6 months			

TRANSAXLE AUTOMATIC 5/1 Capacity: 6,5 liter (Dry fill), Capacity: 2,5 liter (Service fill)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 80000 km/ 48 months		
USE	CLIMATE	
First change only	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 120000 km/ 96 months		

TRANSAXLE MANUAL 6/1 Capacity: 2,4 liter (Dry fill), Capacity: 2,2 lit	er (Service fill)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Change every 120000 km/ 96 months		

# HONDA (EU) CR-V III RE CR-V 2.4I-VTEC 2WD (2007-2011)



HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Change every 36 months		

Change every 36 months

## **POWER STEERING**

Capacity: 1 liter, Capacity: 0,29 liter (Reservoir)

We are unable to give a standard recommendation for this component. Please contact our service department.

Capacity: 7,1-7,2 liter (Dry fill), Capacity: 0,6 liter (Reservuse	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	
Change every 100000 km/ 60 months	·
USE	CLIMATE
First change only	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	

Change every 200000 km/ 120 months

### **AIRCONDITIONING**

Capacity: 440-490 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

### AIRCONDITIONING COMPRESSOR

Capacity: 80-90 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.