

HONDA (EU) LEGEND KA LEGEND 2.7i 24V (1988-1990)

**ENGINE**

Capacity: 4,5 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Bi-Turbo 20W-50***Change every 10000 km/ 6 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Emperol 10W-40****PRODUCT RECOMMENDATION 2****Bi-Turbo 15W-40****PRODUCT RECOMMENDATION 3****HDX 20W-50***Change every 10000 km/ 6 months***USE**

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Asyntho 5W-30***Change every 10000 km/ 6 months***USE**

Severe

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Bi-Turbo 20W-50***Change every 5000 km/ 3 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Emperol 10W-40****PRODUCT RECOMMENDATION 2****Bi-Turbo 15W-40****PRODUCT RECOMMENDATION 3****HDX 20W-50***Change every 5000 km/ 3 months***USE**

Severe

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Asyntho 5W-30***Change every 5000 km/ 3 months*

HONDA (EU) LEGEND KA LEGEND 2.7i 24V

(1988-1990)



TRANSAXLE AUTOMATIC 4/1

Capacity: 3,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Change every 40000 km/ 48 months*

TRANSAXLE MANUAL 5/1

Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40*Check every 10000 km/ 6 months, change every 40000 km/ 24 months*

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Change every 40000 km/ 48 months*

POWER STEERING

Capacity: 1,7 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

HONDA (EU) LEGEND KA LEGEND 2.7i 24V (1988-1990)



COOLING SYSTEM

Capacity: 7,4 liter (+ automatic transmission/transaxle), Capacity: 7,5 liter (+ manual transmission/transaxle)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

Change every 40000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.