

HONDA (EU) LEGEND KB LEGEND 3.7 V6

(2008-2012)

**ENGINE J37A2/J37A3**

Capacity: 5 liter (Dry fill), Capacity: 4,3 liter (Service fill), Filter capacity: 0,3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---------------------------|---------------------------|--------------------------|
| Presteza MSP 0W-20 | Presteza MSP 0W-30 | Duranza LSP 5W-30 |

*Change every 15000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 2,7-3,1 liter (Clutch chamber), Capacity: 0,73-0,75 liter (Hypoid chamber)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Matic 4026 | | |

Change every 45000 km/ 36 months

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Matic 4026 | | |

*Change every 30000 km/ 24 months***TRANSAXLE AUTOMATIC MJBA 5/1**

Capacity: 7,2 liter (Dry fill), Capacity: 2,7 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Matic 4026 | | |

Change every 72000 km/ 72 months

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Matic 4026 | | |

Change every 120000 km/ 96 months

HONDA (EU) LEGEND KB LEGEND 3.7 V6

(2008-2012)



TRANSFERBOX

Capacity: 0,38 liter

| USE | | CLIMATE |
|-----------------------------|-----------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-4 80W-90 | Gearlube GL-5 80W-90 | |

Change every 120000 km/ 96 months

HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|----------------------------------|---------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 |

Change every 36 months

POWER STEERING

Capacity: 1,1 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 8,6 liter (Dry fill), Capacity: 6 liter (Service fill)

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 14+ | | |

Change every 100000 km/ 60 months

| USE | | CLIMATE |
|--------------------------|--|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 14+ | | |

Change every 200000 km/ 120 months

AIRCONDITIONING

Capacity: 450-500 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

HONDA (EU) LEGEND KB LEGEND 3.7 V6 (2008-2012)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.