

HONDA (EU) PRELUDE PRELUDE 1.8 (1986-1990)

**ENGINE ET**

Capacity: 3,5 liter, Filter capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Bi-Turbo 15W-40	HDX 20W-50

Change every 10000 km/ 6 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		

Change every 10000 km/ 6 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Bi-Turbo 15W-40	HDX 20W-50

Change every 5000 km/ 3 months

USE		CLIMATE
Severe		Arctic
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		

*Change every 5000 km/ 3 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 2,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

*Change every 40000 km/ 48 months***TRANSAXLE MANUAL 5/1**

Capacity: 2,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Emperol 10W-40	Bi-Turbo 15W-40

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

HONDA (EU) PRELUDE PRELUDE 1.8 (1986-1990)



HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
<i>Change every 40000 km/ 48 months</i>		

POWER STEERING

Capacity: 1,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES WHEEL BEARINGS REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
<i>Change every 96000 km/ 96 months</i>		

COOLING SYSTEM

Capacity: 6,8-7,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		
<i>Change every 40000 km/ 48 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.