

HONDA (EU) STREAM STREAM 1.7 VTEC

(2002-2006)

**ENGINE D17A**

Capacity: 3,5 liter (+ automatic transmission/transaxle), Capacity: 3,2 liter (+ manual transmission/transaxle), Capacity: 4,2 liter (Dry fill), Filter capacity: 0,2 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---------------------------|--------------------------|--------------------------|
| Presteza MSP 0W-20 | Avanza MSP 0W-30 | Helar 0W-40 |

Change every 20000 km/ 12 months

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---------------------------|--------------------------|--------------------------|
| Presteza MSP 0W-20 | Avanza MSP 0W-30 | Helar 0W-40 |

Change every 10000 km/ 6 months

TRANSAXLE AUTOMATIC 4/1

Capacity: 6 liter (Dry fill), Capacity: 2,7 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Matic 2032 | | |

Check every 20000 km/ 12 months, change every 80000 km/ 48 months

TRANSAXLE MANUAL 5/1

Capacity: 1,9 liter (Dry fill), Capacity: 1,8 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Gear 5015 | | |

Check every 60000 km/ 48 months, change every 120000 km/ 72 months

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS

Capacity: 0,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|----------------------------------|---------------------------|--------------------------|
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 |

Check every 20000 km/ 12 months, change every 36 months

POWER STEERING ELECTRONIC/HYDRAULIC

We are unable to give a standard recommendation for this component. Please contact our service department.

HONDA (EU) STREAM STREAM 1.7 VTEC

(2002-2006)



COOLING SYSTEM

Capacity: 4 liter (+ automatic transmission/transaxle), Capacity: 4,1 liter (+ manual transmission/transaxle)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 20000 km/ 12 months, change every 100000 km/ 60 months

USE

First change only

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 20000 km/ 12 months, change every 200000 km/ 120 months

AIRCONDITIONING

Capacity: 500-550 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

Capacity: 130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.