

HYUNDAI (USA) ELANTRA MD/UD

ELANTRA 2.0 GDI (129 KW) (2014-2016)

**ENGINE** Nu

Capacity: 4,5 liter (Dry fill), Capacity: 4 liter (Service fill), Filter capacity: 0,3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------|--------------------------|
| Duranza ECO 5W-20 | Presteza MSP 5W-30 | Duranza LSP 5W-30 |

Change every 7500 miles/ 12 months

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------|--------------------------|
| Duranza ECO 5W-20 | Presteza MSP 5W-30 | Duranza LSP 5W-30 |

*Change every 3750 miles/ 6 months***TRANSAXLE AUTOMATIC** A6MF1-1 6/1

Capacity: 7,1 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Matic 4036 | | |

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Matic 4036 | | |

*Change every 60000 miles***TRANSAXLE MANUAL** M6CF3-1 6/1

Capacity: 1,9-2 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| SP Gear 5015 | Syngear 75W-90 | |

Check every 37500 miles/ 30 months

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| SP Gear 5015 | Syngear 75W-90 | |

Check every 37500 miles/ 30 months, change every 75000 miles

HYUNDAI (USA) ELANTRA MD/UD

ELANTRA 2.0 GDI (129 KW) (2014-2016)



HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

| USE | | CLIMATE |
|----------------------------------|---------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 |

Check every 30000 miles/ 24 months

COOLING SYSTEM

Capacity: 6 liter (Manual transmission), Capacity: 5,9 liter (with automatic transmission)

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |

Change every 30000 miles/ 24 months

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |

Change every 120000 miles/ 120 months

AIRCONDITIONING COMPRESSOR

Capacity: 90-110 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 475-525 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.