

# HYUNDAI (USA) SANTA FE CM SANTA FE

## 3.3 4X2 (2007-2008)

**ENGINE**

Capacity: 5,2 liter (Service fill)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Bi-Turbo 15W-40</b>	<b>Bi-Turbo 20W-50</b>	

*Change every 7500 miles/ 6 months*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza ECO 5W-20</b>	<b>Asyntho 5W-30</b>	<b>Emperol 10W-40</b>

*Change every 7500 miles/ 6 months*

USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Bi-Turbo 15W-40</b>	<b>Bi-Turbo 20W-50</b>	

*Change every 3000 miles/ 3 months*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza ECO 5W-20</b>	<b>Asyntho 5W-30</b>	<b>Emperol 10W-40</b>

*Change every 3000 miles/ 3 months***TRANSAXLE AUTOMATIC**

Capacity: 10,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4026</b>		

*Check every 15000 miles/ 12 months*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4026</b>		

*Change every 30000 miles*

# HYUNDAI (USA) SANTA FE CM SANTA FE

## 3.3 4X2 (2007-2008)



### HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

Check every 30000 miles/ 24 months

### POWER STEERING

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

Check every 30000 miles/ 24 months

### COOLING SYSTEM

Capacity: 7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

Change every 30000 miles/ 24 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

Change every 60000 miles/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.