

HYUNDAI (EU) ACCENT / PONY / EXCEL LC/MC ACCENT 1.5 CRDI LC (2003-2006)

**ENGINE D3EA**

Capacity: 4,8 liter, Filter capacity: 0,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| Asyntho 5W-30 | Bi-Turbo 15W-40 | |

*Change every 15000 km/ 12 months***TRANSAXLE MANUAL M5CF2 5/1**

Capacity: 2,2 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| SP Gear 5015 | Syngear 75W-90 | |

*Check every 15000 km/ 12 months, change every 45000 km/ 36 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|----------------------------------|---------------------------|--------------------------|
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 |

*Check every 15000 km/ 12 months, change every 24 months***POWER STEERING**

Capacity: 0,75 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| ATF Dexron II-D | | |

GREASE POINTS/NIPPLES

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---------------------------------|------------------------------|--|
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | |

HYUNDAI (EU) ACCENT / PONY / EXCEL LC/MC ACCENT 1.5 CRDI LC (2003-2006)

**COOLING SYSTEM**

Capacity: 5,5-5,8 liter

| USE | | CLIMATE |
|-------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant -38 Organic NF | | |

Check every 15000 km/ 12 months, change every 45000 km/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.