

# HYUNDAI (EU) ACCENT / PONY / EXCEL LC/MC ACCENT / PONY / EXCEL 1.5I 16V (1999-2002)

**ENGINE G4FK**

Capacity: 3 liter, Filter capacity: 0,5 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 15000 km/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Emperol 5W-40**

## PRODUCT RECOMMENDATION 2

**Emperol 10W-40**

## PRODUCT RECOMMENDATION 3

**Bi-Turbo 15W-40***Change every 15000 km/ 12 months*

| USE    | CLIMATE       |
|--------|---------------|
| Severe | Mediterranean |

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 7500 km/ 6 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

## PRODUCT RECOMMENDATION 1

**Emperol 5W-40**

## PRODUCT RECOMMENDATION 2

**Emperol 10W-40**

## PRODUCT RECOMMENDATION 3

**Bi-Turbo 15W-40***Change every 7500 km/ 6 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 6,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Matic 4026***Check every 30000 km/ 24 months, change every 90000 km/ 72 months***TRANSAXLE MANUAL 5/1**

Capacity: 2,15 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Gear 1011**

## PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90**

## PRODUCT RECOMMENDATION 3

**Syngear 75W-90***Check every 15000 km/ 12 months, change every 45000 km/ 36 months*

# HYUNDAI (EU) ACCENT / PONY / EXCEL LC/MC ACCENT / PONY / EXCEL 1.5I 16V (1999-2002)



## HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Drauliquid DOT 3</b>  |  |          |

Check every 15000 km/ 12 months, change every 120000 km/ 24 months

## POWER STEERING

Capacity: 0,9 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>ATF Dexron II-D</b>   |  |          |

Check every 15000 km/ 12 months

## GREASE POINTS/NIPPLES WHEEL BEARINGS REAR

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Check every 15000 km/ 12 months

## COOLING SYSTEM

Capacity: 5,5 liter

| USE                           |  | CLIMATE  |
|-------------------------------|--|----------|
| Normal                        |  | Moderate |
| PRODUCT RECOMMENDATION 1      |  |          |
| <b>Coolant -38 Organic NF</b> |  |          |

Check every 15000 km/ 12 months, change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.