PRODUCT RECOMMENDATION

# HYUNDAI (EU) ACCENT / PONY / EXCEL LC/MC PONY / EXCEL 1.5I (1992-1994)

## ENGINE
Capacity: 3 liter, Filter capacity: 0,4 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Bi-Turbo 20W-50** | | |

*Change every 15000 km/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Emperol 5W-40** | **Asyntho 5W-30** | **Emperol 10W-40** |

*Change every 15000 km/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Severe | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Bi-Turbo 20W-50** | | |

*Change every 7500 km/ 6 months*

| USE | | CLIMATE |
|---|---|---|
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Emperol 5W-40** | **Asyntho 5W-30** | **Emperol 10W-40** |

*Change every 7500 km/ 6 months*

## TRANSAXLE AUTOMATIC 4/1
Capacity: 4,5 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **SP Matic 4026** | | |

*Change every 30000 km/ 24 months*

## TRANSAXLE MANUAL 4/1
Capacity: 1,7 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **SP Gear 5015** | **Syngear 75W-90** | |

*Change every 30000 km/ 24 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# HYUNDAI (EU) ACCENT / PONY / EXCEL LC/MC PONY / EXCEL 1.5I (1992-1994)

## TRANSAXLE MANUAL 5/1
Capacity: 1,8 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **SP Gear 5015** | **Syngear 75W-90** | |

*Change every 30000 km/ 24 months*

## HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Drauliquid DOT 3** | | |

*Change every 30000 km/ 24 months*

## POWER STEERING
Capacity: 0,9 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **ATF Dexron II-D** | | |

## GREASE POINTS/NIPPLES WHEEL BEARINGS REAR

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

*Check every 15000 km/ 12 months*

## COOLING SYSTEM
Capacity: 5,3 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Coolant -38 Organic NF** | | |

*Change every 45000 km/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367