PRODUCT RECOMMENDATION

HYUNDAI (EU) EQUUS / CENTENNIAL VI EQUUS / CENTENNIAL 3.8 V6 GDI (248 KW) (2014-2016)

ENGINE Lambda

Capacity: 6 liter (Dry fill), Capacity: 5,5 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	**Duranza LSP 5W-30**	**Armado Synth LSP Ultra 5W-30**

Check every 500 km, change every 15000 km/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	**Duranza LSP 5W-30**	**Armado Synth LSP Ultra 5W-30**

Check every 500 km, change every 7500 km/ 6 months

DIFFERENTIAL REAR

Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	**Syngear TDL 75W-90**	**Syngear 75W-90**

Check every 48 months/ 60000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	**Syngear TDL 75W-90**	**Syngear 75W-90**

Check every 60000 km/ 48 months, change every 120000 km

TRANSMISSION AUTOMATIC A8LR1 8/1

Capacity: 9,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Change every 90000 km

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

HYUNDAI (EU) EQUUS / CENTENNIAL VI EQUUS / CENTENNIAL 3.8 V6 GDI (248 KW) (2014-2016)

HYDRAULIC BRAKE SYSTEM
Capacity: 0,7-0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	**Drauliquid DOT 3**

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

POWER STEERING
Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 15000 km/ 12 months

COOLING SYSTEM
Capacity: 10,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	**Coolant SP 12**	

Change every 30000 km/ 24 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	**Coolant SP 12**	

Check every 60000 km/ 48 months, change every 210000 km/ 120 months

AIRCONDITIONING COMPRESSOR
Capacity: 110-130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a
Capacity: 675-725 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367