

# HYUNDAI (EU) I30 GD (ROW) I30 1.6 CRDI DPF (94 KW) (2012-2014)

**ENGINE (U-SERIES)**

Capacity: 5,7 liter (Dry fill), Capacity: 5,3 liter (Service fill), Filter capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza MSP 0W-30</b>	<b>Presteza MSP 0W-30</b>	<b>Helar SP LL-03 0W-30</b>

*Change every 10000 km/ 12 months*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza MSP 0W-30</b>	<b>Presteza MSP 0W-30</b>	<b>Helar SP LL-03 0W-30</b>

*Change every 5000 km/ 6 months***TRANSAXLE AUTOMATIC A6MF1 6/1**

Capacity: 7,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

*Check every 48 months/ 60000 km*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

*Check every 60000 km/ 48 months, change every 100000 km***TRANSAXLE MANUAL M6CF3-1 6/1**

Capacity: 1,8-2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 5015</b>	<b>Syngear 75W-90</b>	

*Check every 48 months/ 60000 km*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 5015</b>	<b>Syngear 75W-90</b>	

*Check every 60000 km/ 48 months, change every 120000 km*

# HYUNDAI (EU) I30 GD (ROW) I30 1.6 CRDI DPF (94 KW) (2012-2014)



## HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

Check every 15000 km/ 12 months

## COOLING SYSTEM

Capacity: 6,5 liter (with automatic transmission), Capacity: 6,4 liter (with manual transmission)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

Change every 30000 km/ 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

Check every 60000 km/ 48 months, change every 210000 km/ 120 months

## AIRCONDITIONING COMPRESSOR

Capacity: 140-160 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM R-1234yf

Capacity: 475-525 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM R-134a

Capacity: 475-525 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.