

HYUNDAI (EU) I30 GD (ROW) I30 1.6 MPI (2014-2015)

**ENGINE** Gamma

Capacity: 4 liter (Dry fill), Capacity: 3,6 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Emperol 10W-40*Check every 500 km, change every 15000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 2

Duranza LSP 5W-30

PRODUCT RECOMMENDATION 3

Armado Synth LSP Ultra 5W-30*Check every 500 km, change every 15000 km/ 12 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Emperol 10W-40*Check every 500 km, change every 7500 km/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 2

Duranza LSP 5W-30

PRODUCT RECOMMENDATION 3

Armado Synth LSP Ultra 5W-30*Check every 500 km, change every 7500 km/ 6 months***TRANSAXLE AUTOMATIC** A6GF1 6/1

Capacity: 7,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 48 months/ 60000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 60000 km/ 48 months, change every 100000 km*

HYUNDAI (EU) I30 GD (ROW) I30 1.6 MPI (2014-2015)


TRANSAXLE MANUAL M6CF1 6/1

Capacity: 1,8-1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081*Check every 48 months/ 60000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081*Check every 60000 km/ 48 months, change every 120000 km*
HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Check every 15000 km/ 12 months*
COOLING SYSTEM

Capacity: 6,5 liter (with automatic transmission), Capacity: 6,4 liter (with manual transmission)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12*Change every 40000 km/ 24 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12*Check every 60000 km/ 48 months, change every 200000 km/ 120 months*
AIRCONDITIONING COMPRESSOR

Capacity: 140-160 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

HYUNDAI (EU) I30 GD (ROW) I30 1.6 MPI (2014-2015)



AIRCONDITIONING SYSTEM R-1234yf

Capacity: 475-525 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 475-525 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.