HYUNDAI (EU) I30 GD (ROW) I30 2.0 GDI (2014-2015)



ENGINE Capacity: 4,5 liter (Dry fill), Capacity: 4 liter (Service fill), Filter capacity: 0,3 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Presteza MSP 5W-30	Duranza LSP 5W-30	Helar MSP+ 5W-40		
Check every 500 km, change every 150	000 km/ 12 months			
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Presteza MSP 5W-30	Duranza LSP 5W-30	Helar MSP+ 5W-40		
Check every 500 km, change every 7500 km/ 6 months				

TRANSAXLE AUTOMATIC A6MF1 6/1 Capacity: 7,1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Check every 48 months/ 60000 km			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Check every 60000 km/ 48 months, change every 100000 km			

TRANSAXLE MANUAL M6CF3-1 6/1 Capacity: 1,9-2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Gear 1081			
Check every 48 months/ 60000 km			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
SP Gear 1081			
Check every 60000 km/ 48 months, change every 120000 km			

HYUNDAI (EU) 130 GD (ROW) 130 2.0 GDI (2014-2015)



HYDRAULIC BRAKE/CLUTCH SYSTEM
Capacity: 0,7-0,8 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3

Check every 15000 km/ 12 months

Capacity: 6,5 liter (with automatic t use	ual transmission) CLIMATE	
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Change every 40000 km/ 48 month	ins in the second secon	
USE		CLIMATE
First change only		Moderate

Coolant SP 15+	Coolant SP 12		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
First change only		Moderate	
USE		CLIMATE	

Check every 60000 km/48 months, change every 200000 km/120 months

AIRCONDITIONING COMPRESSOR

Capacity: 140-160 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-1234yf

Capacity: 475-525 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 475-525 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.