

HYUNDAI (EU) I30 GDE (EU) I30 1.6 GDI (99 KW) (2012-2014)

**ENGINE G4FD**

Capacity: 4 liter (Dry fill), Capacity: 3,6 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Specialsynth MSP 5W-40	Helar 0W-40

Check every 500 km, change every 30000 km/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Specialsynth MSP 5W-40	Helar 0W-40

Check every 500 km, change every 15000 km/ 6 months

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Duranza ECO 5W-20	Asyntho 5W-30	

Check every 500 km, change every 10000 km/ 6 months

USE	CLIMATE
Severe (alternative)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Duranza ECO 5W-20	Asyntho 5W-30	

*Check every 500 km, change every 5000 km/ 6 months***TRANSAXLE AUTOMATIC 6/1**

Capacity: 7,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 48 months/ 60000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 60000 km/ 48 months, change every 90000 km

HYUNDAI (EU) I30 GDE (EU) I30 1.6 GDI (99 KW) (2012-2014)



TRANSAXLE MANUAL 6/1

Capacity: 1,8-1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	

Check every 48 months/ 60000 km

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	

Check every 60000 km/ 48 months, change every 120000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 30000 km/ 24 months

COOLING SYSTEM

Capacity: 6,5 liter (with automatic transmission), Capacity: 6,4 liter (with manual transmission)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 30000 km/ 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 60000 km/ 48 months, change every 210000 km/ 120 months

AIRCONDITIONING COMPRESSOR

Capacity: 140-160 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

HYUNDAI (EU) I30 GDE (EU) I30 1.6 GDI (99 KW) (2012-2014)



AIRCONDITIONING SYSTEM R-1234yf

Capacity: 475-525 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 475-525 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.