

# HYUNDAI (EU) IX20 JC IX20 1.6 CRDI (85 KW) (2015-2018)

**ENGINE D4FB**

Capacity: 5,7 liter (Dry fill), Capacity: 5,3 liter (Service fill), Filter capacity: 0,5 liter

USE	CLIMATE
Preferred	Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Check every 500 km, change every 30000 km/ 24 months*

USE	CLIMATE
Severe (preferred)	Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Change every 15000 km/ 12 months*

USE	CLIMATE
Alternative (acceptable)	Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 2

**Bi-Turbo 15W-40***Check every 500 km, change every 20000 km/ 12 months*

USE	CLIMATE
Alternative, severe	Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 2

**Bi-Turbo 15W-40***Change every 10000 km/ 6 months***TRANSAXLE MANUAL M6CF3-1 6/1**

Capacity: 1,9-2 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1081***Check every 48 months/ 60000 km*

USE	CLIMATE
Severe	Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1081***Change every 120000 km*

# HYUNDAI (EU) IX20 JC IX20 1.6 CRDI (85 KW) (2015-2018)



## HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

Change every 30000 km/ 24 months

## COOLING SYSTEM

Capacity: 6,4-6,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

Change every 30000 km/ 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

Check every 60000 km/ 48 months, change every 210000 km/ 120 months

## AIRCONDITIONING COMPRESSOR

Capacity: 90-110 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM R-134a

Capacity: 525-575 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.