HYUNDAI (EU) IX20 JC IX20 1.6 CRDI (95 KW) DPF (2015-2018)



| ENGINE D4FB Capacity: 5,7 liter (Dry fill), Capacity: 5,3 liter (Service fill), Filter capacity: 0,5 liter | | | |
|---|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Preferred | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Helar SP LL-03 5W-30 | Presteza MSP 5W-30 | Meganza MSP 5W-30 | |
| Check every 500 km, change every 300 | 000 km/ 24 months | | |
| USE | | CLIMATE | |
| Severe (preferred) | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Helar SP LL-03 5W-30 | Presteza MSP 5W-30 | Meganza MSP 5W-30 | |
| Change every 15000 km/ 12 months | | | |
| USE | | CLIMATE | |
| Alternative (acceptable) | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Helar SP LL-03 0W-30 | Helar SP LL-03 5W-30 | Presteza MSP 5W-30 | |
| Check every 500 km, change every 200 | 000 km/ 12 months | | |
| USE | | CLIMATE | |
| Alternative, severe | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Helar SP LL-03 0W-30 | Helar SP LL-03 5W-30 | Presteza MSP 5W-30 | |
| Change every 10000 km/ 6 months | | · · · | |

| TRANSAXLE MANUAL M6CF3-1 6/1 Capacity: 1,9-2 liter | | |
|---|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Gear 1081 | | |
| Check every 48 months/ 60000 km | | |

| USE | CLIMATE |
|--------------------------|----------|
| Severe | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Gear 1081 | |
| Change every 120000 km | |

HYUNDAI (EU) IX20 JC IX20 1.6 CRDI (95 KW) DPF (2015-2018)



| use Normal | | climate Moderate |
|---------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 |

Change every 30000 km/ 24 months

| COOLING SYSTEM Capacity: 6,4-6,5 liter | | |
|---|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |
| Change every 30000 km/ 24 months | | |

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |
| | | |

Check every 60000 km/ 48 months, change every 210000 km/ 120 months

AIRCONDITIONING COMPRESSOR Capacity: 90-110 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a Capacity: 525-575 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.