

# HYUNDAI (EU) IX35 / TUCSON EL/LM IX35

## 2.0 CRDI VGT HP 4WD (2010-2014)

**ENGINE (R-SERIES)**

Capacity: 9,6 liter (Dry fill), Capacity: 8 liter (Service fill), Filter capacity: 0,7 liter

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 15W-40***Check every 500 km, change every 30000 km/ 24 months*

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Helar 0W-40**

## PRODUCT RECOMMENDATION 2

**Asyntho 5W-30***Check every 500 km, change every 30000 km/ 24 months*

## USE

Severe

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 15W-40***Check every 500 km, change every 15000 km/ 12 months*

## USE

Severe

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Helar 0W-40**

## PRODUCT RECOMMENDATION 2

**Asyntho 5W-30***Check every 500 km, change every 15000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 0,65 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1011**

## PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90**

## PRODUCT RECOMMENDATION 3

**Syngear 75W-90***Check every 48 months/ 60000 km*

## USE

Severe

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1011**

## PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90**

## PRODUCT RECOMMENDATION 3

**Syngear 75W-90***Check every 60000 km/ 48 months, change every 120000 km*

# HYUNDAI (EU) IX35 / TUCSON EL/LM IX35

## 2.0 CRDI VGT HP 4WD (2010-2014)

**TRANSAXLE AUTOMATIC A6LF2 6/1**

Capacity: 7,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

*Change every 90000 km***TRANSAXLE MANUAL M6GF2 6/1**

Capacity: 1,8-1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 5015</b>	<b>Syngear 75W-90</b>	

*Check every 48 months/ 60000 km*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 5015</b>	<b>Syngear 75W-90</b>	

*Check every 60000 km/ 48 months, change every 120000 km***TRANSFERBOX**

Capacity: 0,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	<b>Syngear 75W-90</b>

*Check every 48 months/ 60000 km*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	<b>Syngear 75W-90</b>

*Check every 60000 km/ 48 months, change every 120000 km*

# HYUNDAI (EU) IX35 / TUCSON EL/LM IX35

## 2.0 CRDI VGT HP 4WD (2010-2014)



### HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

Change every 30000 km/ 24 months

### COOLING SYSTEM

Capacity: 8,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

Change every 30000 km/ 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

Check every 60000 km/ 48 months, change every 210000 km/ 120 months

### AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

### AIRCONDITIONING SYSTEM R-134a

Capacity: 485-535 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.