

HYUNDAI (EU) LANTRA / ELANTRA J1

LANTRA / ELANTRA 1.6i (1992-1995)

**ENGINE** Beta

Capacity: 4,4 liter (Initial fill), Capacity: 3,7 liter (Service fill), Filter capacity: 0,4 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 15000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-40

PRODUCT RECOMMENDATION 2

Asyntho 5W-30

PRODUCT RECOMMENDATION 3

Emperol 10W-40*Change every 15000 km/ 12 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 7500 km/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-40

PRODUCT RECOMMENDATION 2

Asyntho 5W-30

PRODUCT RECOMMENDATION 3

Emperol 10W-40*Change every 7500 km/ 6 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026*Change every 30000 km/ 24 months***TRANSAXLE MANUAL 5/1**

Capacity: 1,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Syngear 75W-90*Change every 30000 km/ 24 months*

HYUNDAI (EU) LANTRA / ELANTRA J1

LANTRA / ELANTRA 1.6i (1992-1995)



HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
<i>Change every 30000 km/ 24 months</i>		

POWER STEERING

Capacity: 0,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
<i>Check every 15000 km/ 12 months</i>		

GREASE POINTS/NIPPLES WHEEL BEARINGS REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
<i>Check every 15000 km/ 12 months</i>		

COOLING SYSTEM

Capacity: 6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		
<i>Change every 45000 km/ 24 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.