

HYUNDAI (EU) SANTA FE DM SANTA FE 2.2 CRDI VGT (2012-2014)

**ENGINE (R-SERIES)**

Capacity: 7,3-7,8 liter (Dry fill), Capacity: 6,3-6,7 liter (Service fill), Filter capacity: 0,7 liter

USE

Normal, fuel according to EN 590

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 15W-40*Check every 500 km, change every 30000 km/ 24 months*

USE

Normal, fuel according to EN 590

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

PRODUCT RECOMMENDATION 2

Asyntho 5W-30*Check every 500 km, change every 30000 km/ 24 months*

USE

Severe

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 15W-40*Check every 500 km, change every 15000 km/ 12 months*

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

PRODUCT RECOMMENDATION 2

Asyntho 5W-30*Check every 500 km, change every 15000 km/ 12 months***TRANSAXLE AUTOMATIC A6LF3 6/1**

Capacity: 7,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Change every 90000 km*

HYUNDAI (EU) SANTA FE DM SANTA FE 2.2 CRDI VGT (2012-2014)


TRANSAXLE MANUAL M6LF1 6/1

Capacity: 1,8-1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	

Check every 48 months/ 60000 km

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	

Check every 60000 km/ 48 months, change every 120000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,7-0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 30000 km/ 24 months

POWER STEERING

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 24 months/ 30000 km

HYUNDAI (EU) SANTA FE DM SANTA FE 2.2

CRDI VGT (2012-2014)

**COOLING SYSTEM**

Capacity: 9,1-9,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 30000 km/ 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 60000 km/ 48 months, change every 210000 km/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.