

# HYUNDAI (EU) SONATA EF SONATA 2.7I V6 (2001-2005)

**ENGINE**

Capacity: 4,5 liter

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 15000 km/ 12 months*

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Emperol 5W-40**

## PRODUCT RECOMMENDATION 2

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 3

**Emperol 10W-40***Change every 15000 km/ 12 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 7,8 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Matic 4026***Check every 30000 km/ 24 months, change every 90000 km/ 72 months***HYDRAULIC BRAKE SYSTEM**

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

## PRODUCT RECOMMENDATION 3

**Drauliquid DOT 3***Change every 120000 km/ 24 months***POWER STEERING**

Capacity: 0,9 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**ATF Dexron II-D***Check every 15000 km/ 12 months*

# HYUNDAI (EU) SONATA EF SONATA 2.7I V6 (2001-2005)



## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## COOLING SYSTEM

Capacity: 7 liter

| USE                           |  | CLIMATE  |
|-------------------------------|--|----------|
| Normal                        |  | Moderate |
| PRODUCT RECOMMENDATION 1      |  |          |
| <b>Coolant -38 Organic NF</b> |  |          |

*Change every 36 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*