

# INFINITI (USA) G35 V35 G35 COUPE V35 (2003-2003)

**ENGINE VQ35HR**

Capacity: 5,4 liter (Dry fill), Filter capacity: 0,3 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 2

**Emperol 10W-40***Change every 3750 miles/ 3 months***DIFFERENTIAL REAR**

Capacity: 1,4 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90***Check every 15000 miles/ 12 months*

## USE

Severe

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90***Change every 30000 miles/ 24 months***TRANSMISSION AUTOMATIC 5/1**

Capacity: 10,3 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Matic 4026***Check every 15000 miles/ 12 months*

## USE

Severe

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Matic 4026***Change every 30000 miles/ 24 months*

# INFINITI (USA) G35 V35 G35 COUPE V35 (2003-2003)



## TRANSMISSION MANUAL 6/1

Capacity: 2,9 liter

| USE                      |                          | CLIMATE                   |
|--------------------------|--------------------------|---------------------------|
| Normal                   |                          | Moderate                  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
| <b>SP Gear 1011</b>      | <b>SP Gear 5015</b>      | <b>Syngear TDL 75W-90</b> |

Check every 15000 miles/ 12 months

| USE                      |                          | CLIMATE                   |
|--------------------------|--------------------------|---------------------------|
| Severe                   |                          | Moderate                  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
| <b>SP Gear 1011</b>      | <b>SP Gear 5015</b>      | <b>Syngear TDL 75W-90</b> |

Change every 30000 miles/ 24 months

## HYDRAULIC BRAKE SYSTEM

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Drauliquid DOT 3</b>  |  |          |

Check every 15000 miles/ 12 months

## POWER STEERING

Capacity: 1 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       | <b>ATF Dexron II-D</b>   |

Check every 30000 miles/ 24 months

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Severe                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       | <b>ATF Dexron II-D</b>   |

Check every 7500 miles/ 12 months

## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

# INFINITI (USA) G35 V35 G35 COUPE V35 (2003-2003)



## COOLING SYSTEM

Capacity: 0,8 liter (Reservoir), Capacity: 8,7 liter (Total)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 14+***Change every 30000 miles/ 24 months*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 14+***Change every 60000 miles/ 48 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.