JAGUAR (EU) XF X250 XF 3.0 V6 (2010-2012)



Duranza LSP 5W-30	Asyntho 5W-30	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Severe		Moderate
USE		CLIMATE
Change every 16000 km/ 12 months		
Duranza LSP 5W-30	Asyntho 5W-30	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
ENGINE Capacity: 6,5 liter		

Change every 8000 km/ 6 months

DIFFERENTIAL REAR Capacity: 0,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

TRANSMISSION AUTOMATIC ZF 6HP26 6/1			
Capacity: 9,5 liter			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
SP Matic 4026			

Check every 16000 km/ 12 months, change every 240000 km/ 120 months

HYDRAULIC BRAKE SYSTEM ABS			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Drauliquid-LV Super DOT 4			
Check every 16000 km/ 12 months, change every 36 months			

JAGUAR (EU) XF X250 XF 3.0 V6 (2010-2012)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
ATF Almirol	

Check every 16000 km/ 12 months

COOLING SYSTEM Capacity: 9,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 16000 km/ 12 months, change every 240000 km/ 120 months

AIRCONDITIONING

Capacity: 750 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

Capacity: 130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.