

# JAGUAR (EU) XF X250 XF 3.0D V6 (177 KW)

## DPF (2012-2015)

**ENGINE**

Capacity: 7,7 liter (Dry fill), Capacity: 6,6 liter (Service fill)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Presteza MSP 5W-30****PRODUCT RECOMMENDATION 2****Elvado LSP 5W-30****PRODUCT RECOMMENDATION 3****Avanza MSP+ 5W-30***Change every 26000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 0,85 liter (Dry fill), Capacity: 0,82 liter (Service fill)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90****PRODUCT RECOMMENDATION 3****Syngear 75W-90****TRANSMISSION AUTOMATIC ZF 6HP28 6/1**

Capacity: 10,1 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 4026****TRANSMISSION AUTOMATIC ZF 8HP70 8/1**

Capacity: 8,5 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 2034****USE**

Severe

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 2034***Change every 48000 km*

# JAGUAR (EU) XF X250 XF 3.0D V6 (177 KW) DPF (2012-2015)



## HYDRAULIC BRAKE SYSTEM ABS

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4***Change every 36 months*

## POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

PRODUCT RECOMMENDATION 2

**ATF Almirol**

## COOLING SYSTEM

Capacity: 12,3 liter (Dry fill), Capacity: 9 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12**

PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF***Change every 260000 km/ 120 months*

## AIRCONDITIONING

Capacity: 725-775 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING COMPRESSOR

Capacity: 110 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*