

JAGUAR (EU) XF X260 XF 35T (2015-2017)**ENGINE**

Capacity: 8,75 liter (Initial fill), Capacity: 7,25 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Presteza MSP 0W-20***Change every 26000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 0,9-1 liter (Initial fill), Capacity: 0,85-0,9 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION AUTOMATIC ZF 8HP45 8/1

Capacity: 8,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2034****USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2034***Change every 48000 km***HYDRAULIC BRAKE SYSTEM****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4***Change every 36 months*

JAGUAR (EU) XF X260 XF 35T (2015-2017)**COOLING SYSTEM**

Capacity: 13,5 liter (Initial fill), Capacity: 7,8-8,3 liter (Service fill)

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | Coolant SP 12 | |

Change every 260000 km/ 120 months

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| Alternative (acceptable) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

Change every 260000 km/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.