

JAGUAR (EU) XJ X351 XJ 3.0 V6 AWD (2012-2014)



ENGINE

Capacity: 8 liter (Dry fill), Capacity: 6,5 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

Change every 16000 km/ 12 months

USE

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-20

Change every 16000 km/ 12 months

DIFFERENTIAL FRONT

Capacity: 0,35 liter (Dry fill), Capacity: 0,33 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90

DIFFERENTIAL REAR

Capacity: 0,85 liter (Dry fill), Capacity: 0,82 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90

DIFFERENTIAL REAR ELECTRONIC LIMITED SLIP

Capacity: 1,22-1,25 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear LS 1015

JAGUAR (EU) XJ X351 XJ 3.0 V6 AWD (2012-2014)



TRANSFERBOX

Capacity: 0,62 liter (Dry fill), Capacity: 0,5 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081*Change every 130000 km/ 60 months*

TRANSMISSION AUTOMATIC ZF 8HP70 8/1

Capacity: 8,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2034

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2034*Change every 48000 km*

HYDRAULIC BRAKE SYSTEM ABS

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 36 months*

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

JAGUAR (EU) XJ X351 XJ 3.0 V6 AWD (2012-2014)

**COOLING SYSTEM**

Capacity: 13,5 liter (Dry fill), Capacity: 8,6 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 260000 km/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.