

# JAGUAR (EU) XJ X351 XJ 5.0 V8 (283 KW) (2009-2012)

**ENGINE**

Capacity: 7,25 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Duranza ECO 5W-20***Change every 26000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 0,9 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90****PRODUCT RECOMMENDATION 3****Syngear 75W-90****TRANSMISSION AUTOMATIC ZF 6HP28 6/1**

Capacity: 10,13 liter (Dry fill)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 4026****TRANSMISSION AUTOMATIC ZF 8HP70 8/1**

Capacity: 10 liter (Dry fill)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 2034****USE**

Severe

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 2034***Change every 48000 km*

# JAGUAR (EU) XJ X351 XJ 5.0 V8 (283 KW) (2009-2012)



## HYDRAULIC BRAKE SYSTEM ABS

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4***Change every 36 months*

## POWER STEERING

Capacity: 1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

PRODUCT RECOMMENDATION 2

**ATF Almirol**

## COOLING SYSTEM

Capacity: 12,5 liter (Dry fill), Capacity: 7,5 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12**

PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF***Change every 260000 km/ 120 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.