JEEP (EU) COMMANDER XK COMMANDER 5.7 HEMI V8 (AWD) (2006-2007)



ENGINE HEMI Capacity: 6,6 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Duranza ECO 5W-20	Helar SP LL-03 5W-30	Presteza MSP 5W-30	
Change every 12000 km/ 6 months			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Duranza ECO 5W-20	Helar SP LL-03 5W-30	Presteza MSP 5W-30	
Change every 5000 km/ 3 months			

DIFFERENTIAL FRONT C200F Capacity: 1,7 liter	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 24000 km	

DIFFERENTIAL FRONT LIMITED SLIP C200FE Capacity: 1,9 liter		
USE	CLIMATE	
Severe	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		
Change every 24000 km	'	

DIFFERENTIAL REAR C213R Capacity: 2,07 liter	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 24000 km	

JEEP (EU) COMMANDER XK COMMANDER 5.7 HEMI V8 (AWD) (2006-2007)



DIFFERENTIAL REAR LIMITED SLIP C213RE Capacity: 2,24 liter	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 24000 km	

TRANSFERBOX NV 140 Capacity: 0,65 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	
Change every 48000 km/ 24 months	<u>'</u>

TRANSFERBOX NV 245 Capacity: 1,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	
Change every 48000 km/24 months	'

TRANSMISSION AUTOMATIC 545RFE 5/1 Capacity: 13,3 liter (Dry fill), Capacity: 6,2 liter (Service fill)		
USE	CLIMATE	
Severe	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 96000 km	·	

HYDRAULIC BRAKE/CLUTCH SYSTEM		
CLIMATE		
Moderate		

JEEP (EU) COMMANDER XK COMMANDER 5.7 HEMI V8 (AWD) (2006-2007)



POWER STEERING			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Fluid 3013			

Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Normal		Moderate	
USE		CLIMATE	
GREASE POINTS/NIPPLES			

COOLING SYSTEM Capacity: 13,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		
Check every 1 months, change every	160000 km/ 60 months	

Check every 1 months, change every 160000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.