JEEP (EU) PATRIOT MK74 PATRIOT 2.0 CRD 4X4 (2007-2010)



ENGINE VW (PD) Capacity: 4,5-4,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	
Change every 15000 km/ 12 months		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	
Change every 30000 km/ 24 months		

DIFFERENTIAL REAR Capacity: 0,6 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

TRANSAXLE MANUAL Aisin Warner BG6 6/1 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 75000 km		

TRANSFERBOX Capacity: 0,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	

JEEP (EU) PATRIOT MK74 PATRIOT 2.0 CRD 4X4 (2007-2010)



HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 12 months, change every 24 months		

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	

COOLING SYSTEM Capacity: 9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant SP 12 EVO
Change every 60000 km/ 60 month	1S	

AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM Capacity: 510 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.