PRODUCT RECOMMENDATION

KIA (EU) CERATO / SPECTRA LD CERATO / SPECTRA 1.6 CRDI VGT (2006-2008)

ENGINE D4FB
Capacity: 5,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Asyntho 5W-30	**Dieselfleet CD+ 15W-40**	**Bi-Turbo 15W-40**

Change every 15000 km/ 12 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Asyntho 5W-30	**Dieselfleet CD+ 15W-40**	**Bi-Turbo 15W-40**

Change every 7500 km/ 6 months

TRANSAXLE MANUAL 5/1
Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
SP Gear 5015	**Syngear 75W-90**	

Check every 15000 km/ 12 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
SP Gear 5015	**Syngear 75W-90**	

Check every 15000 km/ 12 months, change every 90000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM
Capacity: 0,7-0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	**Drauliquid DOT 3**

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KIA (EU) CERATO / SPECTRA LD CERATO / SPECTRA 1.6 CRDI VGT (2006-2008)

POWER STEERING
Capacity: 0,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 24 months/ 30000 km

COOLING SYSTEM
Capacity: 6,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	**Coolant SP 12**	

Check every 15000 km/ 12 months, change every 45000 km/ 24 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	**Coolant SP 12**	

Check every 15000 km/ 12 months, change every 90000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367