

KIA (EU) PICANTO TA PICANTO 1.0 CVVT (2011-2017)

**ENGINE K1.0**

Capacity: 3,2 liter (Dry fill), Capacity: 2,9 liter (Service fill), Filter capacity: 0,2 liter

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Emperol 10W-40

Check every 500 km, change every 15000 km/ 12 months

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		

Check every 500 km, change every 15000 km/ 12 months

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Duranza LSP 5W-30	Asyntho 5W-30

Check every 500 km, change every 15000 km/ 12 months

USE	CLIMATE
Alternative, severe	Mediterranean

PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		

Check every 500 km, change every 7500 km/ 6 months

USE	CLIMATE
Alternative, severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Duranza LSP 5W-30	Asyntho 5W-30

Check every 500 km, change every 7500 km/ 6 months

USE	CLIMATE
Preferred, severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Emperol 10W-40

Check every 500 km, change every 7500 km/ 6 months

KIA (EU) PICANTO TA PICANTO 1.0 CVVT (2011-2017)

**TRANSAXLE AUTOMATIC A4CF0 4/1**

Capacity: 5,7 liter

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026*Check every 60000 km/ 48 months, change every 90000 km*

USE	CLIMATE
Filled for life	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026*Check every 48 months/ 60000 km***TRANSAXLE MANUAL M5EF2 5/1**

Capacity: 1,9-2 liter

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081*Check every 60000 km/ 48 months, change every 120000 km*

USE	CLIMATE
Filled for life	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081*Check every 48 months/ 60000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM ABS**

Capacity: 0,7-0,8 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Check every 15000 km/ 12 months, change every 30000 km/ 24 months*

KIA (EU) PICANTO TA PICANTO 1.0 CVVT (2011-2017)



COOLING SYSTEM

Capacity: 5,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 30000 km/ 24 months, change every 30000 km/ 24 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 60000 km/ 48 months, change every 210000 km/ 120 months

AIRCONDITIONING

Capacity: 345-395 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

Capacity: 90-130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.