KIA (EU) RIO UB RIO 1.1 CRDI (2011-2014)



ENGINE Capacity: 5 liter (Dry fill), Capacity: 4,8 liter	r (Service fill), Filter capacity: 0,5 liter	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Asyntho 5W-30	Bi-Turbo 15W-40
Check every 500 km, change every 15000	km/ 12 months	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Asyntho 5W-30	Bi-Turbo 15W-40
Check every 500 km, change every 7500 km	km/ 6 months	

TRANSAXLE MANUAL M6CF1 6/ Capacity: 1,8-1,9 liter	1	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	
01 000001		

Check every 60000 km, change every 120000 km

USE		CLIMATE
Filled for life		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	
Check every 60000 km	'	<u> </u>

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS Capacity: 0,7-0,8 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3		
Check every 12 months				

KIA (EU) RIO UB RIO 1.1 CRDI (2011-2014)



COOLING SYSTEM Capacity: 6,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Change every 30000 km/24 month	ns	
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Check every 60000 km/ 48 months	, change every 210000 km/ 120 months	

AIRCONDITIONING

Capacity: 445-495 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

Capacity: 110-130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.