## KIA (EU) SOUL AM SOUL 1.6 CRDI VGT (2009-2011)



ENGINE D4FB Capacity: 5,3 liter (Service fill), Filter capacity: 0,5 liter			
	CLIMATE		
	Moderate		
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Dieselfleet CD+ 15W-40	Bi-Turbo 15W-40		
	PRODUCT RECOMMENDATION 2		

Change every 20000 km/ 12 months

TRANSAXLE AUTOMATIC A4CF2 4/1 Capacity: 6,6 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Check every 48 months/ 60000 km		
USE	CLIMATE	
Severe	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Check every 60000 km/ 48 months, chan	e every 90000 km	

TRANSAXLE MANUAL M5CF3 5. Capacity: 1,9 liter	/1		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Syngear 75W-90		
011			

Check every 15000 km/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3	
Check every 15000 km/ 12 months, ch	ange every 30000 km/ 24 months	·	

## KIA (EU) SOUL AM SOUL 1.6 CRDI VGT



(2009-2011)

COOLING SYSTEM Capacity: 7,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Change every 40000 km/ 48 month	s	
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Change every 100000 km/ 60 mont	ths	,

## AIRCONDITIONING COMPRESSOR Capacity: 150 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.